

RADIAN

Smallest IFM+ADM Laser Tracker



Smart 3D/6D measurement

Combining on-board intelligence with durability and accuracy the **Radian** excels at delivering the most accurate and reliable measurements possible in advanced applications.

FEATURES & BENEFITS



Portability and Flexibility

At less than 9 kg, the Radian sensor can be mounted in any orientation and weighs less than 21 kg fully packed.



Interferometer (IFM) Technology

Built-in Interferometer (IFM) provides unparalleled distance measurement precision as an on-board dimensional reference.



Absolute Distance Measurement (ADM)

High-speed ADM laser supplements the IFM for rapid beam reacquisition with no minimum measurement distance.



6DoF and Target Solutions

Radian interfaces with a range of targeting options including 6 Degree of Freedom (6DoF) Active Target, touch probes, and volumetric scanners.



iVision Video Detection

The iVision camera features video streaming and capture for remote monitoring of measurements and documenting the inspection process.



iVision Autolock Capability

iVision offers Manual, Single, or Multi-Selection target lock-on modes for automated measurement processes.



Virtual Level

The high-accuracy internal level establishes a gravity coordinate frame with just one click.



Environmental Compensation

The Radian's onboard high-accuracy weather station ensures accuracy in different operating conditions from -10° C to 45° C.



Service and Support

The Automated Precision global team provides consistent support anywhere in the world.



API AUTOMATED
PRECISION

Technical specifications and descriptions may be subject to change. ©2016 Automated Precision Inc. Revision EN.04.16


Automated Precision Europe GmbH | Im Breitspiel 17 | 69126 Heidelberg | +49 (0) 6221 729 805 0 | info.eu@apisensor.com | www.apisensor.com

RADIAN

Smallest IFM+ADM Laser Tracker

PRODUCT SPECIFICATIONS

[Metric Units]



*Measurement of a ScaleBar per ASME B89.4.19-2006

**Specifications are listed in MPE

Laser Safety: Class II (IEC60825-1)

Range of Measurements

Linear Range (Diameter) 50 m (100 m)
80 m (160 m) *optional*
20 m (40 m) *optional*

Minimum Measurement Distance 0 m
Azimuth Range ± 320° (640° end to end)
Elevation Range -59° to 79°
Internal Level Range ± 2°

3D Measurement Performance

Volumetric Accuracy (IFM) ± 10 µm + 5 µm/m*

Angular Performance

Axial Angular Accuracy 3.5 µm/m**
Maximum Angular Speed 180° / sec
Maximum Angular Acceleration 180° / sec²
Internal Level Accuracy ± 2 arcseconds

Linear Performance

IFM Accuracy ± 0.5 µm/m**
ADM (Lock-on) Accuracy ± 10 µm **or** 0.7 µm/m**
(whichever is greater)

I-Vision Performance

Field of View 30° (diagonal)
Acquisition Range 2 m up to 40 m

Environmental

Operating Temperature -10° C to 45° C
Relative Humidity 10-95% non-condensing
Altitude -700 m to 3000 m

Dimensions

Tracker Weight 9 kg
Tracker Size 177 x 177 x 355 mm
Controller Weight 3.2 kg
Controller Size 110 x 160 x 310 mm

Controller

Communication Protocol Ethernet

In-Line Distance Measurement

| Range | MPE |
|-----------|----------|
| 2 to 5 m | 0.002 mm |
| 2 to 10 m | 0.004 mm |
| 2 to 20 m | 0.009 mm |
| 2 to 50 m | 0.024 mm |
| 2 to 80 m | 0.039 mm |



Scale Bar Measurement

| Range | MPE |
|-------|----------|
| 2 m | 0.028 mm |
| 5 m | 0.049 mm |
| 10 m | 0.085 mm |
| 20 m | 0.156 mm |
| 50 m | 0.368 mm |
| 80 m | 0.580 mm |



The **ASME B89.4.19-2006 standard** prescribes a series of tests for evaluating the performance of spherical measurement systems. These values represent the Maximum Permissible Error (MPE) between a verified Scale Bar and the expected performance of the instrument.

API AUTOMATED PRECISION

Technical specifications and descriptions may be subject to change. ©2016 Automated Precision Inc. Revision EN.04.16

Automated Precision Europe GmbH | Im Breitspiel 17 | 69126 Heidelberg | +49 (0) 6221 729 805 0 | info.eu@apisensor.com | www.apisensor.com